



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
H04N 5/45

A1

(11) International Publication Number:

WO 96/13120

(43) International Publication Date:

2 May 1996 (02.05.96)

(21) International Application Number: PCT/US95/13646

(22) International Filing Date: 5 October 1995 (05.10.95)

(30) Priority Data:
328,674 25 October 1994 (25.10.94) US

(71) Applicant: THOMSON CONSUMER ELECTRONICS, INC.
[US/US]; 10330 North Meridian Street, Indianapolis, IN
46290-1024 (US).

(72) Inventor: SHAFER, Kirk, Edward; 5195 Clear Lake Court,
Carmel, IN 46033 (US).

(74) Agents: TRIPOLI, Joseph, S. et al.; GE & RCA Licensing
Management Operation, Inc.; CN 5312, Two Independence
Way, Princeton, NJ 08540 (US).

(81) Designated States: CN, JP, KR, MX, SG, European patent
(AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).

Published


With international search report.

Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.

BEST AVAILABLE COPY

AVAILABLE COPY

(54) Title: USE OF AN AUDIO PROCESSING CHANNEL IN A TELEVISION RECEIVER DURING A MULTIPICTURE MODE OF OPERATION



(57) Abstract

A television receiver comprises a graphics generator (200), a video processor (242; 252), an audio processor (244; 254), a picture-in-picture processor (230), and a controller (210) for producing a display of an array (100) of inset images. The controller (210) causes one inset image of the array (100) of inset images to be displayed with an associated graphics image to indicate selection of the one inset image, and causes the reproduction of the audio signal associated with said selected inset image. In one embodiment, all images except the selected one are "frozen", and the selected image is updated in near real time. In another embodiment, a second tuner (250) is tuned to the selected-image channel and is used to provide audio for the selected image, while the first tuner (240) continues to sequentially tune the channels from which all of the images are derived.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

USE OF AN AUDIO PROCESSING CHANNEL IN A TELEVISION RECEIVER DURING A MULTIPICTURE MODE OF OPERATION

5 The subject invention generally concerns "multipix" displays for electronics equipment, such as, television receivers, and specifically relates to a novel use for the audio channel during such a multipix display.

 Multipix displays comprising an array of inset images
10 are well-known in the television art. For example, a television receiver having multiplex capability is the RCA CTC-172, manufactured by Thomson Consumer Electronics, Inc., Indianapolis, Indiana. A viewer can call up such a multipix
15 display and can see samples of television programs from a number (usually 12) of channels, simultaneously. The CTC-172 also has the capability of highlighting a particular inset image to indicate its selection by a user, and then leaving the multipix
mode to tune the selected channel. In such multipix receivers, the
20 tuner is repeatedly and sequentially tuned to each of the source channels in order to update each of the inset images. In a perfect world this updating procedure would occur so quickly that the user would be totally unaware that he was viewing samples of each channel. Unfortunately, tuning to each channel and obtaining the video signal sample takes an amount of time which is readily
25 observable to the user. That is, it may take several seconds before the tuner gets around to updating a particular image of an array of twelve inset images. One may also like to hear the sound associated with the selected channel, but due to the relatively slow update speed, this was heretofore impossible.

30 A television receiver comprises a graphics generator, a video processor, an audio processor, a picture-in-picture processor, and a controller for producing a display of an array of inset images. The controller causes one inset image of the array of inset images to be displayed with an associated graphics image to
3.5 indicate selection of the one inset image, and causes the reproduction of the audio signal associated with said selected inset

image. In one embodiment, all images except the selected one are "frozen", and the selected image is updated in near real time. In another embodiment, a second tuner is tuned to the selected-image channel and is used to provide audio for the selected image, while the first tuner continues to sequentially tune the channels from which all of the images are derived.

FIGURE 1 shows a screen display comprising a multipicture display.

FIGURE 2 shows, in block diagram form, the relevant portion of the circuitry of a television receiver operating in accordance with the invention.

FIGURE 3 is a simplified drawing of a remote control unit suitable for use with the invention.

Referring to FIGURE 1, a twelve picture multipix array is displayed on a screen 100 of a television receiver. A graphical highlight is shown forming a border around the inset image bearing the channel number 29. The graphical border can be moved from inset to inset by means of cursor keys of a remote control unit 300 of FIGURE 3. During the time that the inset array is displayed, CHAN UP, CHAN DN, VOL UP, and VOL DN keys 303, 304, 305, and 306 are no longer used to change channels or for volume control, but rather are used as X and Y-direction cursor control keys for use by the viewer to "navigate" through the array.

A user operates cursor keys 303-306 to highlight an inset image, and then presses MENU key 301 to accomplish the selection of that particular inset image for tuning. In accordance with the subject invention, highlighting an inset image also causes the reproduction of the audio associated with the channel from which that inset was derived. There are two applications for this concept. In the first, the tuner is commanded to stop sequentially tuning channels for video sample updating, and to tune instead to the channel associated with the selected inset image. All other channel samples are "frozen", by virtue of the fact that they are not being updated, but the selected inset can be updated at a much faster rate, near real time. The audio can be used from the

tuner because it is continuously tuned to the same channel in this mode of operation. It is probable that something of interest on the selected inset caught the viewers eye, and caused him to make that particular selection. The result is that the viewer can see a frozen snapshot of what is on all channels and can focus his attention on the near real time updated video and continuous audio of the selected inset image.

In the second application, a two tuner television receiver uses one tuner for repeatedly and sequentially updating the array of inset images, and uses the second tuner to tune continuously to the selected channel from which the selected inset image is derived. The result in this case is that the viewer can see a continual updates of what is on all channels, but can nevertheless focus his attention on the video and audio of the selected inset image.

FIGURE 2 shows a simplified block diagram of that section of the receiver which provides the above-described screen display and audio capability. OSD (On Screen Display) Processor 200 is preferably a bit-mapped graphics generator for creating the graphics borders around the highlighted inset images, under control of a Main Microprocessor 210. OSD Processor 200 produces image signals at Red, Green, and Blue color signal output terminals. Main Microprocessor 210 also receives a video signal from the television chassis and derives closed caption information therefrom. It produces closed caption display signals at Red, Green, and Blue color signal output terminals. The outputs of OSD Processor 200 and of Main Microprocessor 210 are summed together in an array of summing circuits, generally designated 215. These summing circuits may comprise, for example, the well-known non-additive mixer circuit, which has the property that it will pass the greater of the two signals at its inputs while blocking the lesser of the two input signals. The outputs of the summing circuits are applied to a MAIN VIDEO PROCESSOR unit 220 which also receives Y (luminance) and C (chrominance) component video signals from a PIP unit 230. The input signals for PIP unit 230 are provided by a first tuner 240, a first video

processor 242, a second tuner 250, and a second video processor 252. A fast switch signal generated by either OSD Processor 200 or Main Microprocessor 210 causes the graphics signal (or closed caption signal) to be substituted for the video signal for the duration of the fast switching signal. Tuner 240 and tuner 250 also provide signals to a pair of audio processors 244 and 254. Audio processors 244 and 254 provide signals to an audio switching arrangement 260 operating under control of main microprocessor 210. The selected audio signal is applied to an audio amplifier 270 and to a speaker 280 (the audio channel is shown monophonic for simplicity, but stereophonic is not precluded.)

A one tuner embodiment would include all elements of FIGURE 2 except tuner 240, video processor 242, audio processor 244, and audio switch 260. In operation of the one tuner embodiment, Main Microprocessor (i.e., system controller) 210 operating under control of its own software causes PIP unit 230 to automatically display a graphics border drawn by OSD processor 200 around the exact location of the PIP inset corresponding to the user's selection, and controls tuner 250 to stop sequentially tuning, and to tune continuously to the channel from which the selected inset image is derived. When tuner 250 has completed tuning that channel, the output of audio processor 254 is applied to amplifier 270 for audio reproduction in speaker 280. Audio amplifier is also controllable to turn on and off by main microprocessor 210 via the internal bus.

In operation of the two tuner embodiment, Main Microprocessor (i.e., system controller) 210 operating under control of its own software causes PIP unit 230 to automatically display a graphics border drawn by OSD processor 200 around the exact location of the PIP inset corresponding to the user's selection, and controls tuner 240 to tune to the channel from which the selected inset image is derived. When tuner 240 has completed tuning that channel, audio switch 260 is caused to select the output of audio processor 244 and apply it to amplifier 270 for audio reproduction in speaker 280. Audio amplifier is

5

also controllable to turn on and off by main microprocessor 210 via the internal bus. As a further advantage, it is noted that faster tuning of the selected channel can be accomplished because the second tuner is already tuned to the selected channel.

5 The phrases "system controller" and main microprocessor are used interchangeably herein and are intended to also encompass microcomputers and dedicated custom integrated circuits. The term "television receiver" is intended to encompass television receivers having a display device
10 (commonly called TV sets) and television receivers not having a display device (such as VCRs).

CLAIMS

1. Apparatus for use in a television system, apparatus
5 comprising:
 - graphics generation means (200) for generating a graphics signal for display;
 - video processing means (242;220) for processing a video signal;
 - 10 audio processing means (244;270) for processing an audio signal;
 - picture-in-picture processing means (230) coupled to said video processing means (242;220) and deriving a signal from said video signal for producing an inset image;
 - 15 said video processing means (242;220) producing a combined signal which when displayed comprises a video image of an array of inset images (100); and
 - control means (210) for controlling said video processing means (242;220), said graphics generation means (200)
 - 20 and said picture-in-picture processing means(230);
 - said control means (210) causing one inset image of said array of inset images to be displayed and causing said audio processing means to reproduce an audio signal associated with said selected inset image.

7

2. The television apparatus of claim 1 further comprising a tuner (240) for tuning television channels in a repeating sequence for providing recurring samples of video signals at different television channels;

5 said audio processing means (244;270) processes audio signals received from said tuner;

 said video processing means (242;220) processing a first video signal received from said tuner (240) and a second video signal received from said picture-in-picture processing
10 means (230) for producing said combined signal;

 said array of inset images (100) are sampled from said different television channels; and

 said control means (210) controlling said tuner (240) and causing one inset image of said array of inset images to be
15 displayed with a graphics image to indicate selection of said one inset image, and causing said tuner (240) to tune to the channel of said selected inset image and controlling said audio processor to reproduce an audio signal associated with said selected inset
image.

20

3. The television apparatus of claim 1 further comprising:

a first tuner (240) for tuning television channels; and
a second tuner (250) for tuning television channels in
5 a repeating sequence for providing recurring samples of video signals at different television channels; and wherein

said audio processing means (244;254;260;270) processes audio signals received from said first tuner;

said video processing means comprises a first video
10 processor (242) for processing a video signal received from said first tuner (240) and a second video processor (252) for processing a video signal received from said second tuner (250) and a third video processor (220) coupled to said picture-in-picture processing means (230) for producing said combined
15 signal;

said array of inset images (100) are sampled from said different television channels; and

said control means (210) controlling said first (240) and second (250) tuners;

20 said control means (210) causing one inset image of said array of inset images to be displayed with a graphics image to indicate selection of said one inset image, and causing said first tuner to tune to the channel of said selected inset image and controlling said audio processor to reproduce an audio signal
25 associated with said selected inset image.





Fig. 1

Fig. 2



3/3




Fig. 3

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 95/13646

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04N5/45

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 13 no. 374 (E-808) ,18 August 1989 & JP,A,01 126083 (SANYO ELECTRIC CO LTD) 18 May 1989, see abstract	1-3
Y	EP,A,0 617 556 (SONY EUROPA GMBH) 28 September 1994 see column 10, line 37 - column 11, line 40 see column 15, line 53 - column 20, line 11 see column 32, line 55 - column 33, line 10	1-3
Y	US,A,4 903 129 (BELL I. ET AL) 20 February 1990 see the whole document	1-3
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- (*) document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

& document member of the same patent family

Date of the actual completion of the international search

1 March 1996

Date of mailing of the international search report

06.03.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Verschelden, J

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 95/13646

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 486 987 (TECNOENERGIA BY TEL S.R.L.) 27 May 1992 see the whole document ---	1-3
A	EP,A,0 557 033 (SONY CORPORATION) 25 August 1993 see the whole document ---	1-3
A	GB,A,2 220 543 (SAMSUNG ELECTRONICS CO. LTD) 10 January 1990 see the whole document ---	1-3
A	GB,A,2 260 873 (CANON KABUSHIKI KAISHA) 28 April 1993 see the whole document ---	1-3
A	EP,A,0 376 376 (N.V. PHILIPS GLOEILAMPENFABRIEKEN) 4 July 1990 see the whole document ---	1-3
A	US,A,4 845 564 (HAKAMADA K. ET AL) 4 July 1989 see the whole document ---	1-3
A	US,A,5 296 918 (KIM J.) 22 March 1994 see the whole document ---	1-3
A	GB,A,2 275 585 (SONY CORPORATION) 31 August 1994 see line W. ---	1-3
A	US,A,5 237 418 (KANEKO T.) 17 August 1993 see the whole document ---	1-3
A	DE,A,41 21 314 (THOMSON CONSUMER ELECTRONICS) 2 January 1992 see the whole document ---	1-3
A	PATENT ABSTRACTS OF JAPAN vol. 6 no. 140 (E-121) ,29 July 1982 & JP,A,57 063981 (TOSHIBA CORP) 17 April 1982. see abstract -----	1-3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 95/13646

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0617556	28-09-94	FI-A- 941313 JP-A- 7226983	23-09-94 22-08-95
US-A-4903129	20-02-90	JP-A- 2294171	05-12-90
EP-A-0486987	27-05-92	IT-B- 1241293	29-12-93
EP-A-0557033	25-08-93	JP-A- 5236377 US-A- 5414471	10-09-93 09-05-95
GB-A-2220543	10-01-90	NONE	
GB-A-2260873	28-04-93	JP-A- 5113864 AU-B- 653268 AU-B- 2723592	07-05-93 22-09-94 20-05-93
EP-A-0376376	04-07-90	US-A- 4959719 DE-D- 68921859 DE-T- 68921859 ES-T- 2071648 JP-A- 2218277	25-09-90 27-04-95 09-11-95 01-07-95 30-08-90
US-A-4845564	04-07-89	JP-A- 63258174 CA-A- 1298399	25-10-88 31-03-92
US-A-5296918	22-03-94	JP-A- 5211639	20-08-93
GB-A-2275585	31-08-94	JP-A- 6311449	04-11-94
US-A-5237418	17-08-93	JP-A- 4114576	15-04-92
DE-A-4121314	02-01-92	US-A- 5194954 CA-A, C 2042779 CN-A- 1057747 FR-A- 2664453 GB-A, B 2245786 JP-A- 4233876	16-03-93 30-12-91 08-01-92 10-01-92 08-01-92 21-08-92

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☒ **FADED TEXT OR DRAWING**

☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☒ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)